



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 3/16/2010
 Searching for: H20

Del Zotto Mfg. Co.

ACTIVE

Marion

4405 W. Hwy. 40
 Ocala, FL 34482

| TANK NUMBER | CATEGORY | WALL THICKNESS | LIQUID DEPTH | TOP EXTERIOR WIDTH | TOP EXTERIOR LENGTH | EFFECTIVE GALLONS | TOTAL GALLONS | USE | APPROVAL DATE |
|---|----------|----------------|--------------|--------------------|---------------------|-------------------|---------------|-----|---------------|
| 42-007-50D-C4 | C4 | 6.00 | 47.00 | 60 | 96 | 750 | 1,030 | | 7/6/2009 |
| REMARKS: 4" or 6" inlets and outlets, H20 traffic loading rated | | | | | | | | | |
| 42-007-50S-C4 | C4 | 6.00 | 47.00 | 60 | 96 | 750 | 1,030 | | 7/6/2009 |
| REMARKS: 4" or 6" inlets and outlets, H20 traffic loading rated | | | | | | | | | |
| 42-007-51D-C4 | C4 | 6.00 | 44.00 | 72 | 96 | 900 | 1,222 | | 7/6/2009 |
| REMARKS: 4" or 6" inlets and outlets, H20 traffic loading rated | | | | | | | | | |
| 42-007-51S-C4 | C4 | 6.00 | 44.00 | 72 | 96 | 900 | 1,222 | | 7/6/2009 |
| REMARKS: 4" or 6" inlets and outlets, H20 traffic loading rated | | | | | | | | | |
| 42-007-52D-C4 | C4 | 6.00 | 46.00 | 72 | 108 | 1050 | 1,446 | | 7/6/2009 |
| REMARKS: 4" or 6" inlets and outlets, H20 traffic loading rated | | | | | | | | | |
| 42-007-52S-C4 | C4 | 6.00 | 46.00 | 72 | 108 | 1050 | 1,446 | | 7/6/2009 |
| REMARKS: 4" or 6" inlets and outlets, H20 traffic loading rated | | | | | | | | | |
| 42-007-53D-C4 | C4 | 6.00 | 44.00 | 72 | 132 | 1250 | 1,745 | | 7/6/2009 |
| REMARKS: 4" or 6" inlets and outlets, H20 traffic loading rated | | | | | | | | | |
| 42-007-53S-C4 | C4 | 6.00 | 44.00 | 72 | 132 | 1250 | 1,745 | | 7/6/2009 |
| REMARKS: 4" or 6" inlets and outlets, H20 traffic loading rated | | | | | | | | | |
| 42-007-54D-C4 | C4 | 6.00 | 48.00 | 84 | 162 | 2000 | 2,805 | | 7/6/2009 |
| REMARKS: 4" or 6" inlets and outlets, H20 traffic loading rated | | | | | | | | | |
| 42-007-54S-C4 | C4 | 6.00 | 48.00 | 84 | 162 | 2000 | 2,805 | | 7/6/2009 |
| REMARKS: 4" or 6" inlets and outlets, H20 traffic loading rated | | | | | | | | | |
| 42-007-55D-C4 | C4 | 6.00 | 64.00 | 84 | 162 | 2800 | 3,366 | | 7/6/2009 |
| REMARKS: 4" or 6" inlets and outlets, H20 traffic loading rated | | | | | | | | | |
| 42-007-55S-C4 | C4 | 6.00 | 64.00 | 84 | 162 | 2800 | 3,366 | | 7/6/2009 |
| REMARKS: 4" or 6" inlets and outlets, H20 traffic loading rated | | | | | | | | | |
| 42-007-G30D-C | C4 | 6.00 | 56.00 | 116.5 | 150.75 | 3000 | 3,750 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G30S-C4 | C4 | 6.00 | 56.00 | 116.5 | 150.75 | 3000 | 3,888 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G32D-C | C4 | 6.00 | 60.00 | 116.8 | 151 | 3200 | 3,995 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G32S-C4 | C4 | 6.00 | 60.00 | 116.8 | 151 | 3200 | 4,144 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G35D-C | C4 | 6.00 | 65.00 | 117 | 151 | 3500 | 4,297 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 3/16/2010
 Searching for: H20

Del Zotto Mfg. Co.

ACTIVE

Marion

4405 W. Hwy. 40
 Ocala, FL 34482

| TANK NUMBER | CATEGORY | WALL THICKNESS | LIQUID DEPTH | TOP EXTERIOR | | EFFECTIVE GALLONS | TOTAL GALLONS | USE | APPROVAL DATE |
|---|----------|----------------|--------------|--------------|--------|-------------------|---------------|-----|---------------|
| 42-007-G35S-C4 | C4 | 6.00 | 65.00 | 117 | 151 | 3500 | 4,459 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G37D-C | C4 | 6.00 | 68.00 | 117 | 151 | 3700 | 4,478 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G37S-C4 | C4 | 6.00 | 68.00 | 117 | 151 | 3700 | 4,648 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G40D-C | C4 | 6.00 | 73.00 | 117.4 | 151.5 | 4000 | 4,257 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G40S-C4 | C4 | 6.00 | 73.00 | 117.4 | 151.5 | 4000 | 5,111 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G43D-C | C4 | 6.00 | 78.00 | 117.6 | 151.63 | 4300 | 5,093 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G43S-C4 | C4 | 6.00 | 78.00 | 117.6 | 151.63 | 4300 | 5,291 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G45D-C | C4 | 6.00 | 81.00 | 117.9 | 151.88 | 4500 | 5,472 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G45S-C4 | C4 | 6.00 | 81.00 | 117.9 | 151.88 | 4500 | 5,678 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G48D-C | C4 | 6.00 | 69.00 | 117.1 | 187.38 | 4800 | 5,778 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G48S-C4 | C4 | 6.00 | 69.00 | 117.1 | 187.38 | 4800 | 5,951 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G50D-C | C4 | 6.00 | 72.00 | 117.3 | 187.38 | 5000 | 6,006 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G50S-C4 | C4 | 6.00 | 72.00 | 117.3 | 187.38 | 5000 | 6,187 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G53D-C | C4 | 6.00 | 76.00 | 117.5 | 187.63 | 5300 | 6,323 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G53S-C4 | C4 | 6.00 | 76.00 | 117.5 | 187.63 | 5300 | 6,515 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G55D-C | C4 | 6.00 | 78.00 | 117.6 | 187.63 | 5500 | 6,476 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G55S-C4 | C4 | 6.00 | 78.00 | 117.6 | 187.63 | 5500 | 6,674 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 3/16/2010
 Searching for: H20

Del Zotto Mfg. Co.

ACTIVE

Marion

4405 W. Hwy. 40
 Ocala, FL 34482

| TANK NUMBER | CATEGORY | WALL THICKNESS | LIQUID DEPTH | TOP EXTERIOR WIDTH | TOP EXTERIOR LENGTH | EFFECTIVE GALLONS | TOTAL GALLONS | USE | APPROVAL DATE |
|---|----------|----------------|--------------|--------------------|---------------------|-------------------|---------------|-----|---------------|
| 42-007-G58D-C | C4 | 6.00 | 82.00 | 117.9 | 187.88 | 5800 | 7,029 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G58S-C4 | C4 | 6.00 | 82.00 | 117.9 | 187.88 | 5800 | 7,238 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G60D-C | C4 | 6.00 | 73.00 | 117.4 | 217.5 | 6000 | 7,173 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G60S-C4 | C4 | 6.00 | 73.00 | 117.4 | 217.5 | 6000 | 7,357 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G65D-C | C4 | 6.00 | 78.00 | 117.6 | 217.63 | 6500 | 7,628 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G65S-C4 | C4 | 6.00 | 78.00 | 117.6 | 217.63 | 6500 | 7,826 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G70D-C | C4 | 6.00 | 84.00 | 118 | 218 | 7000 | 8,465 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G70S-C4 | C4 | 6.00 | 84.00 | 118 | 218 | 7000 | 8,679 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G75D-C | C4 | 6.00 | 77.00 | 117.5 | 253.63 | 7500 | 8,884 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G75S-C4 | C4 | 6.00 | 77.00 | 117.5 | 253.63 | 7500 | 9,079 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G80D-C | C4 | 6.00 | 81.00 | 117.9 | 253.88 | 8000 | 9,670 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G80S-C4 | C4 | 6.00 | 81.00 | 117.9 | 253.88 | 8000 | 9,876 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G85D-C | C4 | 6.00 | 68.00 | 117.3 | 319.25 | 8500 | 10,173 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G85S-C4 | C4 | 6.00 | 68.00 | 117.3 | 319.25 | 8500 | 10,344 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G90D-C | C4 | 6.00 | 72.00 | 117.3 | 319.38 | 9000 | 10,715 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G90S-C4 | C4 | 6.00 | 72.00 | 117.3 | 319.38 | 9000 | 10,896 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-G95D-C | C4 | 6.00 | 69.00 | 117.1 | 349.38 | 9500 | 11,342 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 3/16/2010
 Searching for: H20

Del Zotto Mfg. Co.

ACTIVE

Marion

4405 W. Hwy. 40
 Ocala, FL 34482

| TANK NUMBER | CATEGORY | WALL THICKNESS | LIQUID DEPTH | TOP EXTERIOR | | EFFECTIVE GALLONS | TOTAL GALLONS | USE | APPROVAL DATE |
|---|----------|----------------|--------------|--------------|--------|-------------------|---------------|-----|---------------|
| 42-007-G95S-C4 | C4 | 6.00 | 69.00 | 117.1 | 349.38 | 9500 | 11,515 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-GA1D-C | C4 | 6.00 | 79.00 | 117.6 | 319.75 | 10000 | 11,687 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-GA1S-C | C4 | 6.00 | 79.00 | 117.6 | 319.75 | 10000 | 11,887 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-GA2D-C | C4 | 6.00 | 83.00 | 118 | 320 | 10500 | 12,669 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-GA2S-C | C4 | 6.00 | 83.00 | 118 | 320 | 10500 | 12,880 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-GA3D-C | C4 | 6.00 | 79.00 | 117.6 | 349.75 | 11000 | 12,853 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-GA3S-C | C4 | 6.00 | 79.00 | 117.6 | 349.75 | 11000 | 13,053 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-GA4D-C | C4 | 6.00 | 83.00 | 118 | 349.88 | 11500 | 13,926 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-GA4S-C | C4 | 6.00 | 83.00 | 118 | 349.88 | 11500 | 14,137 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-GA5D-C | C4 | 6.00 | 78.00 | 117.6 | 385.75 | 12000 | 14,088 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-GA5S-C | C4 | 6.00 | 78.00 | 117.6 | 385.75 | 12000 | 14,286 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-GA6D-C | C4 | 6.00 | 81.00 | 117.9 | 385.88 | 12500 | 15,103 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-GA6S-C | C4 | 6.00 | 81.00 | 117.9 | 385.88 | 12500 | 15,309 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-GA7D-C | C4 | 6.00 | 84.00 | 118 | 386 | 13000 | 15,601 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-GA7S-C | C4 | 6.00 | 84.00 | 118 | 386 | 13000 | 15,815 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-GA8D-C | C4 | 6.00 | 82.00 | 117.9 | 409.88 | 13500 | 16,266 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-GA8S-C | C4 | 6.00 | 82.00 | 117.9 | 409.88 | 13500 | 16,475 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 3/16/2010
 Searching for: H20

Del Zotto Mfg. Co.

ACTIVE

Marion

4405 W. Hwy. 40
 Ocala, FL 34482

| TANK NUMBER | CATEGORY | WALL THICKNESS | LIQUID DEPTH | TOP EXTERIOR WIDTH | TOP EXTERIOR LENGTH | EFFECTIVE GALLONS | TOTAL GALLONS | USE | APPROVAL DATE |
|--|----------|----------------|--------------|--------------------|---------------------|-------------------|---------------|--------|---------------|
| 42-007-GA9D-C | C4 | 6.00 | 78.00 | 117.6 | 445.63 | 14000 | 16,388 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-GA9S-C | C4 | 6.00 | 78.00 | 117.6 | 445.63 | 14000 | 16,586 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-GB1D-C | C4 | 6.00 | 81.00 | 117.9 | 445.88 | 14500 | 17,366 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-GB1S-C | C4 | 6.00 | 81.00 | 117.9 | 445.88 | 14500 | 17,778 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-GB2D-C | C4 | 6.00 | 84.00 | 118 | 446 | 15000 | 18,152 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading- | | | | | | | | | |
| 42-007-GB2S-C | C4 | 6.00 | 84.00 | 118 | 446 | 15000 | 18,366 | | 2/2/2009 |
| REMARKS: Approved for H20 traffic loading | | | | | | | | | |
| 42-007-H01S-C4 | C4 | 6.00 | 50.00 | 65 | 46 | 300 | 400 | Pump t | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover. | | | | | | | | | |
| 42-007-H02D-C4 | C4 | 6.00 | 42.00 | 65 | 103 | 750 | 923 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover. | | | | | | | | | |
| 42-007-H02S-C4 | C4 | 6.00 | 42.00 | 65 | 103 | 750 | 923 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover. | | | | | | | | | |
| 42-007-H03D-C4 | C4 | 6.00 | 50.00 | 65 | 103 | 900 | 1,060 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover. | | | | | | | | | |
| 42-007-H03S-C4 | C4 | 6.00 | 50.00 | 65 | 103 | 900 | 1,060 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover. | | | | | | | | | |
| 42-007-H04D-C4 | C4 | 6.00 | 42.00 | 65 | 141 | 1050 | 1,314 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |
| 42-007-H04S-C4 | C4 | 6.00 | 42.00 | 65 | 141 | 1050 | 1,314 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |
| 42-007-H05D-C4 | C4 | 6.00 | 50.00 | 65 | 141 | 1250 | 1,512 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |
| 42-007-H05S-C4 | C4 | 6.00 | 50.00 | 65 | 141 | 1250 | 1,512 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |
| 42-007-H06D-C4 | C4 | 6.00 | 45.00 | 87 | 113 | 1350 | 1,469 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |
| 42-007-H06S-C4 | C4 | 6.00 | 45.00 | 0 | 113 | 1350 | 1,469 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 3/16/2010
 Searching for: H20

Del Zotto Mfg. Co.

ACTIVE

Marion

4405 W. Hwy. 40
 Ocala, FL 34482

| TANK NUMBER | CATEGORY | WALL THICKNESS | LIQUID DEPTH | TOP EXTERIOR WIDTH | TOP EXTERIOR LENGTH | EFFECTIVE GALLONS | TOTAL GALLONS | USE | APPROVAL DATE |
|--|----------|----------------|--------------|--------------------|---------------------|-------------------|---------------|-----|---------------|
| 42-007-H07D-C4 | C4 | 6.00 | 50.00 | 0 | 0 | 1500 | 1,605 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |
| 42-007-H07S-C4 | C4 | 6.00 | 50.00 | 87 | 113 | 1500 | 1,605 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |
| 42-007-H08D-C4 | C4 | 6.00 | 55.00 | 87 | 113 | 1650 | 1,741 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |
| 42-007-H08S-C4 | C4 | 6.00 | 55.00 | 87 | 0 | 1650 | 1,741 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover. | | | | | | | | | |
| 42-007-H09D-C4 | C4 | 6.00 | 42.00 | 87 | 164 | 1900 | 2,102 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |
| 42-007-H09S-C4 | C4 | 6.00 | 42.00 | 87 | 164 | 1900 | 2,102 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |
| 42-007-H10D-C4 | C4 | 6.00 | 45.00 | 87 | 164 | 2000 | 2,224 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |
| 42-007-H10S-C4 | C4 | 6.00 | 45.00 | 87 | 164 | 2000 | 2,224 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |
| 42-007-H11D-C4 | C4 | 6.00 | 49.00 | 87 | 164 | 2200 | 2,388 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |
| 42-007-H11S-C4 | C4 | 6.00 | 49.00 | 87 | 164 | 2200 | 2,388 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |
| 42-007-H12D-C4 | C4 | 6.00 | 51.00 | 0 | 0 | 2300 | 2,471 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |
| 42-007-H12S-C4 | C4 | 6.00 | 51.00 | 0 | 0 | 2300 | 2,471 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |
| 42-007-H13D-C4 | C4 | 6.00 | 56.00 | 87 | 164 | 2500 | 2,677 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |
| 42-007-H13S-C4 | C4 | 6.00 | 56.00 | 87 | 164 | 2500 | 2,677 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |
| 42-007-H14D-C4 | C4 | 6.00 | 60.00 | 87 | 164 | 2700 | 2,847 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |
| 42-007-H14S-C4 | C4 | 6.00 | 60.00 | 87 | 164 | 2700 | 2,842 | | 3/10/2010 |
| REMARKS: Tank rated for H20 traffic loading and C4 burial cover | | | | | | | | | |



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 3/16/2010
 Searching for: H20

Florida Septic, Inc.

ACTIVE

Alachua

Post Office Box 545
 Hawthorne, FL 32640

| TANK NUMBER | CATEGORY | WALL THICKNESS | LIQUID DEPTH | TOP EXTERIOR WIDTH | TOP EXTERIOR LENGTH | EFFECTIVE GALLONS | TOTAL GALLONS | USE | APPROVAL DATE |
|---|----------|----------------|--------------|--------------------|---------------------|-------------------|---------------|-----|---------------|
| 01-011-02D-C4 | C4 | 4.00 | 52.30 | | | 750 | | | 5/31/2001 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-02S-C4 | C4 | 4.00 | 52.30 | | | 750 | | | 5/31/2001 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-06D-C4 | C4 | 6.00 | 53.00 | | | 750 | | | 10/31/2001 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-06S-C4 | C4 | 6.00 | 53.00 | | | 750 | | | 10/31/2001 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-11D-C4 | C4 | | 44.00 | | | 1050 | 1,348 | | 3/17/2003 |
| REMARKS: Houses Bionest BNC-400 ATU. Wall thickness can be either 4" or 6". AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-11S-C4 | C4 | | 44.00 | | | 1050 | 1,348 | | 3/17/2003 |
| REMARKS: Wall thickness can be either 4" or 6". AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-13D-C4 | C4 | | 52.00 | | | 1250 | 1,564 | | 3/17/2003 |
| REMARKS: Houses Bionest BNC-500 ATU. Wall thickness can be either 4" or 6". AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-13S-C4 | C4 | | 52.00 | | | 1250 | 1,564 | | 3/17/2003 |
| REMARKS: Wall thickness can be either 4" or 6". AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-27D-C4 | C4 | 6.00 | 53.00 | | | 1500 | | | 10/31/2001 |
| REMARKS: Houses Bionest BNC-600 ATU. AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-27S-C4 | C4 | 6.00 | 53.00 | | | 1500 | | | 10/31/2001 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-29D-C4 | C4 | 4.00 | 44.00 | | | 1650 | | | 7/30/2001 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-29S-C4 | C4 | 4.00 | 44.00 | | | 1650 | | | 7/30/2001 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-30D-C4 | C4 | 6.00 | 44.00 | | | 1650 | | | 5/29/2002 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-30S-C4 | C4 | 6.00 | 44.00 | | | 1650 | | | 5/29/2002 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-39D-C4 | C4 | 6.00 | 53.00 | | | 2000 | | | 5/29/2002 |
| REMARKS: Houses Bionest BNC-750 ATU. AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-39S-C4 | C4 | 6.00 | 53.00 | | | 2000 | | | 5/29/2002 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 3/16/2010
 Searching for: H20

Florida Septic, Inc.

ACTIVE

Alachua

Post Office Box 545
 Hawthorne, FL 32640

| TANK NUMBER | CATEGORY | WALL THICKNESS | LIQUID DEPTH | TOP EXTERIOR WIDTH | TOP EXTERIOR LENGTH | EFFECTIVE GALLONS | TOTAL GALLONS | USE | APPROVAL DATE |
|---|----------|----------------|--------------|--------------------|---------------------|-------------------|---------------|-----|---------------|
| 01-011-49D-C4 | C4 | 6.00 | 66.00 | | | 2500 | | | 5/29/2002 |
| REMARKS: Houses Bionest BNC-1000 ATU. AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-49S-C4 | C4 | 6.00 | 66.00 | | | 2500 | | | 5/29/2002 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-53D-C4 | C4 | 6.00 | 42.50 | | | 2800 | | | 10/31/2001 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-53S-C4 | C4 | 6.00 | 42.50 | | | 2800 | | | 10/31/2001 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-57D-C4 | C4 | 6.00 | 45.50 | | | 3000 | | | 10/31/2001 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-57S-C4 | C4 | 6.00 | 45.50 | | | 3000 | | | 10/31/2001 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-60D-C4 | C4 | 6.00 | 60.00 | | | 2300 | | | 5/29/2002 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-60S-C4 | C4 | 6.00 | 60.00 | | | 2300 | | | 5/29/2002 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-65D-C4 | C4 | 6.00 | 49.50 | | | 3300 | | | 10/31/2001 |
| REMARKS: Houses Bionest BNC-1250 ATU. AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-65S-C4 | C4 | 6.00 | 49.50 | | | 3300 | | | 10/31/2001 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-69D-C4 | C4 | 6.00 | 55.00 | | | 3700 | | | 5/29/2002 |
| REMARKS: Houses Bionest BNC-1500 ATU. AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-69S-C4 | C4 | 6.00 | 55.00 | | | 3700 | | | 5/29/2002 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-73D-C4 | C4 | 6.00 | 64.50 | | | 4300 | | | 5/29/2002 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-73S-C4 | C4 | 6.00 | 64.50 | | | 4300 | | | 5/29/2002 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-77D-C4 | C4 | 6.00 | 72.00 | | | 5000 | | | 5/29/2002 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-77S-C4 | C4 | 6.00 | 72.00 | | | 5000 | | | 5/29/2002 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-90D-C4 | C4 | 4.00 | 43.00 | | | 1250 | | | 7/30/2001 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 3/16/2010
 Searching for: H20

Florida Septic, Inc.

ACTIVE

Alachua

Post Office Box 545
 Hawthorne, FL 32640

| TANK NUMBER | CATEGORY | WALL THICKNESS | LIQUID DEPTH | <u>TOP EXTERIOR</u> WIDTH | LENGTH | EFFECTIVE GALLONS | TOTAL GALLONS | USE | APPROVAL DATE |
|--|----------|----------------|--------------|---------------------------|--------|-------------------|---------------|-----|---------------|
| 01-011-90S-C4 | C4 | 4.00 | 43.00 | | | 1250 | | | 7/30/2001 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-92D-C4 | C4 | 6.00 | 46.00 | | | 1350 | | | 10/31/2001 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-92S-C4 | C4 | 6.00 | 46.00 | | | 1350 | | | 10/31/2001 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |
| 01-011-93S-C4 | C4 | 4.00 | 42.00 | | | 300 | | | 12/14/2001 |
| REMARKS: AASHTO H20 traffic loading rated when buried between 18" to 48" | | | | | | | | | |



DEPARTMENT OF HEALTH

STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS

SEPTIC TANK MANUFACTURERS

run date: 3/16/2010

Searching for: H20

Standard Precast

ACTIVE

Duval

PO Box 61839

Jacksonville FL 32236

| TANK NUMBER | CATEGORY | WALL THICKNESS | LIQUID DEPTH | <u>TOP EXTERIOR</u> WIDTH | LENGTH | EFFECTIVE GALLONS | TOTAL GALLONS | USE | APPROVAL DATE |
|---------------|----------|----------------|--------------|---------------------------|--------|-------------------|---------------|-----|---------------|
| 16-145-06D-C4 | C4 | 6.00 | 62.00 | 96 | 152 | 3021 | | | 4/15/2009 |

REMARKS: 2700 gallon septic tank for fire station #28---approved for H20 traffic loading



DEPARTMENT OF HEALTH

STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS

SEPTIC TANK MANUFACTURERS

run date: 3/16/2010

Searching for: H20

U.S. Precast Corporation

ACTIVE

Dade

8351 N.W. 93rd Street

Miami, FL 33166

| TANK NUMBER | CATEGORY | WALL THICKNESS | LIQUID DEPTH | <u>TOP EXTERIOR</u> WIDTH | LENGTH | EFFECTIVE GALLONS | TOTAL GALLONS | USE | APPROVAL DATE |
|---------------|----------|----------------|--------------|---------------------------|--------|-------------------|---------------|-----|---------------|
| 13-094-13S-C3 | C3 | 8.00 | 63.00 | 24 | 192 | 1250 | 1,496 | | 6/19/2007 |

REMARKS: grease trap-8" wall thickness-Rated for H20 traffic loading